



DATA COLLECTION ELECTRIC ROTARY DISTRIBUTOR (SLIP RING)

N° DOC

CUSTOMER	
CUSTOMER DATA	
PRODUCT SECTOR	

OPERATING DATA ELECTRICAL DISTRIBUTOR

AMBIENT	INSIDE		
	OUTSIDE		

AMBIENT TEMPERATURES	C° MIN	
	C° MAX	

PROTECTION REQUIRED	IP	
----------------------------	-----------	--

CLASSIFIED AREA (ATEX)	
-------------------------------	--

PLACEMENT ON THE MACHINE	HORIZONTAL	
	VERTICAL	

ROTATION	SPEED ROTATION (RPM)	
	ACCELERATION (ǰ)	
	ROTATION CONTINUOUS	
	ROTATION DISCONTINUOUS	
	ROTATION INTERMITTENT	

ELEMENT OF ROTATION	PART ROTOR (RINGS)	
	PART STATOR (BRUSHES)	

TYPE OF USE	N°Wey	CORRENTE NONINALE (A)	SUPPLY VOLTAGE (V)	TIPCABLE TYPE	SECTION CABLE mm ²	FACTOR FOR OPERATING%
EARTH						
POWER (> 15 A) (power supply)						
AUXILIARY / CONTROLS (SOLENOID) (<15)						
CONTROLS SIGNAL DIG / ANG , CAN BUS						

MAXIMUM DIMENSIONS OF ELECTRIC COLLECTOR	length (mm)	
	Ø diameter (mm)	

WIRING / ACCESSORIES

SIDE ROTOR (RINGS) (R)	cable length	mt
-------------------------------	--------------	----

SIDE STATOR (BRUSH) S	cable length	mt
------------------------------	--------------	----

ACCESSORIES	CONNECTION WITH FLANGE	dimension
	ANTICONDENSATION RESISTANCE	W